



FOOD SERVICE FOAMING DEGREASER

903

SPECIFICATIONS:

Dilution	Various
pH Level	12.0 – 13.0
Color	No Dyes Added
Fragrance	No Fragrance Added

Use in foaming equipment, dip tanks, steam cleaners, and scrubbers to remove heavy duty oil and fats. Great for cleaning kitchen soils.



High foaming degreaser specifically designed to remove grease and soils in food service areas. Quickly penetrates and suspends animal fats, vegetable oils, butter, greases and food soils. Can be applied with a spray bottle, mop, deck brush, foam gun, auto scrubber or pressure washer. For use in food processing areas and federally inspected meat and poultry plants.

FORMULA FEATURES:

- High Foaming
- Extremely Versatile
- Fast Acting
- Clings to Vertical Surfaces
- Cleans Grease, Vegetable Oils, Animal Fats, Butter
- Removes Heavy Buildup
- Biodegradable

RECOMMENDED FOR:

- Food Processing Areas and Federally Inspected Meat and Poultry Plants
- Floors
- Walls
- Terrazzo
- Marble
- Ceramic Tile
- Engines
- Machinery
- Conveyors
- Concrete, Brick and Stucco
- Appliance Exteriors

DIRECTIONS:

- Dilute with water. Use dilution guide as a starting point depending on the surface to be cleaned. Adjust dilution, as desired, for soil load and other factors.
- After surface has been cleaned, rinse thoroughly with water. (See dilution guide on back).

FOOD SERVICE FOAMING DEGREASER

DIRECTIONS: (CONTINUED)

Regular Uses:**Recommended Dilutions:****Floors, Walls, General Maintenance:**

Light soil	1:50	(2½ oz./gal.)
Medium soil	1:20	(6 oz./gal.)
Heavy soil.....	1:10	(12 oz./gal.)
Air Filters	1:5	(21 oz./gal.)
Engines, Machines, Equipment	1:5	(21 oz./gal.)
Hoods, Flues	1:5	(21 oz./gal.)
Conveyors	1:10	(12 oz./gal.)
Concrete, Brick, Stucco	1:5	(21 oz./gal.)
Light Fixtures, Appliances	1:20	(6 oz./gal.)
Ducts, Grills	1:5	(21 oz./gal.)
Kitchen Walls, Terrazzo, Marble, Ceramic Tile, Asphalt Tile.....	1:20	(6 oz./gal.)