

## HyperL GUARANTEED (three phase)



### Standard equipment:

- 6.601.0001 Gun PRO S'10 3/8" M with quick connection



- 6.602.0044 Lance 900 mm with quick connection.



- 3.103.0053 Nozzle type 060 (mod. 1515 LP)
- 3.103.0050 Nozzle type 045 (mod. 2015 LP)
- 3.103.0054 Nozzle type 065 (mod. 2021 LP)



- 4.618.0143 High pressure hose 10 m



- Power cable 5 m

### Optional:

- Hose-reel with brake (hose not included) cod.6.608.0018

### Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling.
- Three ceramic pistons, brass linear pump head with built-in by-pass valve.
- Integrated elastic joint, for best pump coupling.
- Low voltage and delayed Total Stop.
- Suction and delivery S/S valves.
- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Detergent built-in tank for indirect suction.
- Auxiliary motor for burner air cooling and mechanical two ways fuel pump.
- Hose-reel (optional).



**Integrated elastic joint, for best pump coupling**

**VERSION**  
**60 Hz**  
**AVAILABLE**  
**DETAILS PAGE 33**

	HYPER L 1515 LP	HYPER L 2015 LP	HYPER L 2021 LP
code	8.621.0907	8.621.0908	8.621.0928
operat. pressure	150 bar-2175 psi	200 bar-2900 psi	200 bar-2900 psi
delivery rate	900 l/h-3.96 GPM	900 l/h-3.96 GPM	1260 l/h-5.55 GPM
abs. power/voltage	5500W - 400V~50Hz 3ph	7300W - 400V~50Hz 3ph	9700W - 400V~50Hz 3 ph
motor/pump type/RPM	MPW5/1450 RPM	MPW5/1450 RPM	MPW5/1450 RPM
max. temp. inlet/outlet	40/140 °C	40/140 °C	40/140 °C