

eForce® Scrubber

26-in and 32-in Ride-On Scrubber



The eForce® Scrubber's patented joystick drive system and touch screen controls put everything your operators need right at their fingertips. With superior maneuverability and a generous solution tank, the eForce Scrubber is the perfect scrubber for medium and large facilities.

- Patented joystick drive system makes the eForce Scrubber simple to control and less fatiguing to drive.
- Excellent visibility of work areas.
- The zero turn radius design allows the scrubber to be used up against the wall and in tight areas.
- Training is easy. A training manual is built into the touch screen control panel.
- Dial in exactly what you need for your application. Three solution flow rates, three pad pressures, two pad speeds and two vacuum speeds give you the flexibility you need to maximize your productivity and run time.
- Conservation Mode With one button press, the eForce Scrubber is set to the lowest water and power settings. Perfect for cleaning areas where quiet operation and water conservation is needed.

NSS® Enterprises, Inc. 3115 Frenchmens Road Toledo, Ohio 43607-2958 USA www.nss.com



eForce Scrubber Specifications

Cleaning Path

eForce Scrubber 26 26 in (66 cm) eForce Scrubber 32 32 in (81 cm)

Brush Motors

Power (HP) 0.75

Brush Speed (RPM) 150 or 225

Brush Pressure (lbs) 70, 110, 150 (eForce Scrubber 26) 80, 120, 160 (eForce Scrubber 32)

Vacuum Motor

Type 2-stage tapered fan

Power (HP) 0.60 Water Lift (in) 61 Air Flow (CFM) 78

Solution Pump

Power (HP) 0.125

Flow Rates (GPM) 0.35, 0.70, 1.00

Drive System

Drive Motor (HP) 0.33

Drive Speed Up to 500 ft/min; top reverse 60% forward speed

Drive Wheel 12-in x 4-in, non-marking rubber with slip resistant

tread

Batteries (Runtime) Four 6V 235 AH (3.2 hours)

Four 6V 350 AH (4.3 hours)

Construction

Solution Tank (gal) 25 (94 L) Recovery Tank (gal) 27 (102 L)

Dimensions

Length (in) 56.5 (143 cm)
Width (in) 27 (69 cm)

Height (in) 54 (137 cm)

Sound Level 67 dBA
Weight (lbs) 1,115

Productivity (ft² /hr) 26" - 35,800 Theoretical, 16,600 Practical

32" - 44,100 Theoretical, 20,400 Practical

Warranty 3 years limited, 10 year for tanks



The upper body opens to almost 90 degrees allowing ample space for cleaning out the recovery tank.



A removable filter captures debris before it can clog the recovery tank drain.



Wide-open access to the battery compartment makes filling batteries simple.

Printed in USA



- 1 Touchpad control lets the operator work all of the controls from one screen.
- Supervisor Mode allows you to limit machine operation to only the settings you want available.
- **3** Recovery Tank is easily accessible for thorough cleaning.
- Squeegee swings directly behind the scrub deck to allow for the tightest possible turns.
- **5** Heavy-duty 7-gauge steel frame runs the full length of the machine.
- **6** Optional chemical metering system allows precise dosing of cleaning chemicals to eliminate overuse.
- Side-loaded battery compartment makes battery installation easier.
- No tools are required to change the squeegee blades.



Conservation Mode: With one button press, the eForce Scrubber is set to the lowest water and power settings. Perfect for cleaning areas where quiet operation and water conservation is needed.



NSS Enterprises, Inc.

3115 Frenchmens Road Toledo, OH 43607-2958

P: (800) 677-1663 F: (419) 531-3761

mailus@nss.com www.nss.com

Specifications subject to change without notice.

DISTRIBUTED BY